



- High quality components guarantee the stable refrigeration system;
- Unique and excellent evaporator technique ensures efficient heat transfer effect;
- Heavy-duty overhead crane for moving, lifting and tipping the ice cans;
- Ice can options of galvanized steel or stainless steel;
- Modular design ensures easy installation, operation and maintenance;
- Experienced team of installation and commissioning.

Specification of Block Ice Machine LIB-100B

Item		Specification	Unit
Power supply		380V/3P/50Hz	Voltage/Phase/Frequency
Refrigerant		R22/R404A	
Daily capacity		10000kg/day	
Cooling mode		Water-cooled	
Standard condition	Ambient temperature	35	°C
	Water inlet temperature	25	°C
Operating Power	Compressor	17.86X2	kw
	Cooling tower fan	1.1	kw
	Cooling tower pump	2.2	kw
	Brine agitator reducer	0.75	kw
	Average total	37.6	kw
	Total install power	48	kw

Compressor	Refrigeration capacity	43.8X2	kw
	Condensing temperature	38	°C
	Evaporating temperature	-18	°C
	COP.	2.45	kw/kw
	Horse power	28	HP
	Compressor Nos	2	unit
Ice size range	Weight range	20~100	kg
	Thickness range	100/125/160/220	mm
	Height range	600/800/1000	mm
Ice specification	Dimension	500×160×780	(L×W×H) (mm)
	Weight	50	Kg
	Ice quantity	104	PC
	Harvest times	2	times/day
Period	Ice making time	12	hr/time
	Ice defrost time	10	min/time
Ice machine size	Size	12374×2242×2900	(L×W×H) (mm)
	Net weight	6340	Kg
	Pipe size	1-1/4"	inch
	Water supply pressure requirement	1~6	bar
Cooling tower module size	Cooling tower size	ø2000x2410	(O.D.×H) (mm)
	Feed pipe size	3/4"	inch
	Cooling water pipe size	2-1/2"	inch
	Operating weight	670	Kg
Parts info	Compressor	Bitzer, Germany	
	Expansion valve	ALCO, United States	
	Stop valve	DANFOSS, Denmark	

	Solenoid valve	DANFOSS, Denmark
	Filter	ALCO, United States
	Button/indicator	Schneider, France
	Electrical	Schneider, France
	PLC	SIEMENS, Germany