

- Aluminum plate evaporator directly transfer heat to water, ice making process is fast and efficiency is increased;
- All parts contact with ice or water is made of aluminum alloy or SUS304, ice comply with food hygiene requirement;
- Evaporator use aerospace level specialized aluminum material, high strength and good heat transfer performance;
- Hot freon gas doffing method, realize fast ice doffing process and it only takes 15 minutes;
- Automatic water adding system, more intelligent and easier operation;
- Mechanical design makes taking ice out easier.

## Specification of Block Ice Machine LIB-200D

ltem		Specification	Unit
Power supply		380V/3P/50Hz	Voltage/Phase/Frequency
Refrigerant		F	22/R404A
Daily capacity		20ton/day	
Cooling mode		Water-cooled	
Standard condition	Ambient temperature	35	$^{\circ}\! \mathbb{C}$
	Water inlet temperature	25	$^{\circ}\!$
Operating Power	Compressor	22X3	kw
	Cooling tower fan	2.2	kw
	Cooling tower pump	3	kw
	Lifting mechanism reducer	5.5	kw
	Water adding pump	1.25	kw
	Average total	72	kw

	Total install power	96	kw
Compressor	Refrigeration capacity	55.6X3	kw
	Condensing temperature	38	°C
	Evaporating temperature	-15	°C
	COP.	2.53	kw/kw
	Horse power	34X3	HP
	Compressor Nos	3	unit
Ice size range	Weight range	20~100	kg
	Thickness range	100/125/160/220	mm
	Height range	600/800/1000	mm
	Dimension	560×125×780	(L×W×H) (mm)
las aposification	Weight	50	Kg
Ice specification	Ice quantity	144	PC
	Harvest times	3	times/day
Portod	Ice making time	7.5	hr/time
Period	Ice defrost time	0.5	hr/time
Compressor module size	Dimension	3080×2140×2460	(L×W×H) (mm)
Compressor module size	Net weight	2880	Kg
	Size	8385×2145×2480	(L×W×H) (mm)
Evenerator modulo circo	Net weight	6540	Kg
Evaporator module size	Pipe size	1-1/4"	inch
	Water supply pressure requirement	1~6	bar
	Cooling tower size	Ø2650x2645	(O.D.×H) (mm)
Cooling tower module size	Feed pipe size	1"	inch
	Cooling water pipe size	4"	inch
	Operating weight	1300	Kg

Parts info	Compressor	Bitzer, Germany	
	Expansion valve	ALCO, United States	
	Stop valve	DANFOSS, Denmark	
	Solenoid valve	DANFOSS, Denmark	
	Filter	ALCO, United States	
	Button/indicator	Schneider, France	
	Electrical	Schneider, France	
	PLC	SIEMENS, Germany	