

- Aluminum plate evaporator directly transfer heat to water, ice making process is fast and efficiency is increased;
- All parts contact with ice or water is made of aluminum alloy or SUS304, ice comply with food hygiene requirement;
- Evaporator use aerospace level specialized aluminum material, high strength and good heat transfer performance;
- Hot freon gas doffing method, realize fast ice doffing process and it only takes 15 minutes;
- Automatic water adding system, more intelligent and easier operation;
- Mechanical design makes taking ice out easier.

Specification of Block Ice Machine LIB-250D

ltem		Specification	Unit
Power supply		380V/3P/50Hz	Voltage/Phase/Frequency
Refrigerant		R22/R404A	
Daily capacity		25T/day	
Cooling mode		Water-cooled	
Standard condition	Ambient temperature	35	$^{\circ}\! \mathbb{C}$
	Water inlet temperature	25	$^{\circ}\!$
Operating Power	Compressor	25.6X3	kw
	Cooling tower fan	2.2	kw
	Cooling tower pump	7.5	kw
	Lifting mechanism reducer	6.6	kw
	Water adding pump	1.25	kw
	Average total	88.3	kw

	Total install power	120	kw
Compressor	Refrigeration capacity	68.4X3	kw
	Condensing temperature	38	$^{\circ}\! \mathbb{C}$
	Evaporating temperature	-15	°C
	COP.	2.61	kw/kw
	Horse power	44X3	HP
	Compressor Nos	3	unit
Ice size range	Weight range	20~100	kg
	Thickness range	100/125/160/220	mm
	Height range	600/800/1000	mm
	Dimension	150×160×980	(L×W×H) (mm)
	Weight	20	Kg
Ice specification	Ice quantity	627	PC
	Harvest times	2	times/day
Period	Ice making time	11.5	hr/time
	Ice defrost time	0.5	hr/time
Compressor module size	Dimension	3080×2140×2460	(L×W×H) (mm)
Compressor module size	Net weight	3750	Kg
	Size	10195×2160×2741	(L×W×H) (mm)
Evaporator modulo sizo	Net weight	7560	Kg
Evaporator module size	Pipe size	1-1/4"	inch
	Water supply pressure requirement	1~6	bar
Cooling tower module size	Cooling tower size	ø3050x2780	(O.D.×H) (mm)
	Feed pipe size	1"	inch
	Cooling water pipe size	5"	inch
	Operating weight	1630	Kg

Parts info	Compressor	Bitzer, Germany	
	Expansion valve	ALCO, United States	
	Stop valve	DANFOSS, Denmark	
	Solenoid valve	DANFOSS, Denmark	
	Filter	ALCO, United States	
	Button/indicator	Schneider, France	
	Electrical	Schneider, France	
	PLC	SIEMENS, Germany	