

## Flake Ice Machine LIF-150C

[Home](#) > [Products](#) > [Flake Ice Machine](#)> Containerized Type



- High efficiency heat transfer technology;
- Spiral blade design decreases resistance and friction, flake ice 100% fall off;
- Specialized processing technology ensures long service time evaporator;
- Easy installation, ready to use after water and electric plug in;
- Reliable operation, little maintenance;
- Compact design, less space required;
- Pre-fabricated system, no need to connect pipes and wirings;
- Mobility and flexibility

### Specification of Flake Ice Machine LIF-150C

Item		Specification	Unit
Power supply		380V/3P/50Hz	Voltage/Phase/Frequency
Refrigerant		R22/R404A	
Daily capacity		15000kg/day	
Cooling mode		Water-cooled	
Standard condition	Ambient temperature	35	°C
	Water inlet temperature	25	°C
Operating power	Compressor	21x2	kw
	Cooling tower fan	1.1	kw
	Cooling tower pump	2.2	kw

	Reducer	1.5	kw
	Cooling water pump	0.55	kw
	Average total	48.75	kw
	Total install power	58	kw
Compressor	Refrigeration capacity	43.5x2	kw
	Condensing temperate	38	°C
	Evaporating temperature	-23	°C
	COP.	2.3	kw/kw
	Horse power	40x2	HP
Cooling tower module size	Cooling tower size	ø2000x2410	(O.D.×H) (mm)
	Feed pipe size	3/4"	inch
	Cooling water pipe size	2-1/2"	inch
	Operating weight	670	Kg
Container info	Size	6058x2438x2591	(L×W×H) (mm)
	Operating weight	8000	Kg
Parts info	Compressor	Bitzer, Germany	
	Expansion valve	ALCO, United States	
	Stop valve	DANFOSS, Denmark	
	Solenoid valve	DANFOSS, Denmark	
	Filter	ALCO, United States	
	Button/indicator	Schneider, France	
	Electrical	Schneider, France	
	PLC	SIEMENS, Germany	